


Features

- IEEE 802.11b MAC and Baseband for Supporting Standard Rates up to 11 Mbps
- Wireless Interface Following the IEEE 802.11b Standard
- Wireless LAN MAC Unit with ARM7TDMI® RISC Processor
- Integrated 128-byte Transmit and 128-byte Receive FIFOs for Wireless MAC Layer Functions
- 16-bit PCMCIA Bus Interface
- Glueless SRAM Interface for All MAC Operations, Supporting up to 1M Byte of External Memory
- Integrated 6K x 32-bit Internal SRAM, Used for Fast Program Code Execution and Temporary Storage of Data
- Glueless Flash Memory Interface, Supporting up to 1M Byte of Nonvolatile Memory for Permanent Storage of Program Code
- Wired Equivalency (WEP) in Hardware Supporting 64-bit and 128-bit Encryption
- The Integrated MAC Support Unit (MSU) Supports Timing Critical MAC Functions
- The WLAN and Inter-networking Functions Can be Changed and Updated Easily to New Requirements Since They are Implemented in Microcode
- Supports Automatic Fallback from 11 Mbps to 5.5, 2 and 1 Mbps
- 160-ball BGA Package
- Low-voltage 3.3V Operation
- Internal ROM Contains Hardwired CIS Information for Automatic Configuration when Card is Inserted in the PCMCIA Slot
- SPI Interface and 2 GPIO Pins
- AT76C504 Offers the Option to Download the Whole Code from SPI DataFlash® or an Option to Eliminate Flash by Downloading the Program from the Mass Storage Device
- Integrated 802.11b Baseband Processor
- Baseband Supports Antenna Diversity Algorithm
- Baseband Supports Differential or Single-ended I- and Q-Baseband Signals
- Baseband Supports Japan Filter

Block Diagram



802.11b Media Access Controller (MAC) and Baseband for PCMCIA Bus

AT76C504 Summary

Rev. 2218CS-WLAN-01/03



Note: This is a summary datasheet. A complete datasheet is available under NDA. For more information, please contact your local Atmel Sales Office.

Description

The AT76C504 is a single-chip baseband controller that can handle IEEE 802.11b standard compliant data rates of up to 11 Mbps and provides all processing and functionality needed for the MAC protocol of IEEE 802.11b. AT76C504 provides a glueless interface conforming to PC Card 95 and can support a variety of RF interfaces.

The AT76C504 chip incorporates an ARM7TDMI processor using a sophisticated architecture to control the on-chip peripherals, manage the internal memory and allocate data queue buffers as well as to communicate with the host through the PCMCIA parallel bus. The processor peripheral logic consists of a PCMCIA bus interface, a Serial Peripheral Interface (SPI), a MAC unit, a 802.11b Baseband block, the common memory interface, internal boot Read Only Memory (ROM) and the normal operation stages and common microcontroller blocks like timers, interrupt controller and bus arbiter.

The ARM7TDMI core supports two alternative instruction sets. Powerful 32-bit code can be executed by the processor in ARM® operating mode. However, a 16-bit instruction subset is also available in Thumb® mode. Thumb mode can be selected to exploit full processor power with limited external memory resources. Note that ARM7TDMI operating mode can be changed at run time with negligible overhead.



Atmel Headquarters

Corporate Headquarters

2325 Orchard Parkway
San Jose, CA 95131
USA
TEL 1(408) 441-0311
FAX 1(408) 487-2600

Europe

Atmel Sarl
Route des Arsenaux 41
Case Postale 80
CH-1705 Fribourg
Switzerland
TEL (41) 26-426-5555
FAX (41) 26-426-5500

Asia

Room 1219
Chinachem Golden Plaza
77 Mody Road Tsimshatsui
East Kowloon
Hong Kong
TEL (852) 2721-9778
FAX (852) 2722-1369

Japan

9F, Tonetsu Shinkawa Bldg.
1-24-8 Shinkawa
Chuo-ku, Tokyo 104-0033
Japan
TEL (81) 3-3523-3551
FAX (81) 3-3523-7581

Atmel Operations

Memory

2325 Orchard Parkway
San Jose, CA 95131
TEL 1(408) 441-0311
FAX 1(408) 436-4314

Microcontrollers

2325 Orchard Parkway
San Jose, CA 95131
TEL 1(408) 441-0311
FAX 1(408) 436-4314

La Chantrerie
BP 70602
44306 Nantes Cedex 3, France
TEL (33) 2-40-18-18-18
FAX (33) 2-40-18-19-60

ASIC/ASSP/Smart Cards

Zone Industrielle
13106 Rousset Cedex, France
TEL (33) 4-42-53-60-00
FAX (33) 4-42-53-60-01

1150 East Cheyenne Mtn. Blvd.
Colorado Springs, CO 80906
TEL 1(719) 576-3300
FAX 1(719) 540-1759

Scottish Enterprise Technology Park
Maxwell Building
East Kilbride G75 0QR, Scotland
TEL (44) 1355-803-000
FAX (44) 1355-242-743

RF/Automotive

Theresienstrasse 2
Postfach 3535
74025 Heilbronn, Germany
TEL (49) 71-31-67-0
FAX (49) 71-31-67-2340

1150 East Cheyenne Mtn. Blvd.
Colorado Springs, CO 80906
TEL 1(719) 576-3300
FAX 1(719) 540-1759

Biometrics/Imaging/Hi-Rel MPU/ High Speed Converters/RF Datacom

Avenue de Rochepleine
BP 123
38521 Saint-Egreve Cedex, France
TEL (33) 4-76-58-30-00
FAX (33) 4-76-58-34-80

e-mail

literature@atmel.com

Web Site

<http://www.atmel.com>

© Atmel Corporation 2003.

Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

ATMEL® and DataFlash® are the registered trademarks of Atmel.

ARM7TDMI® and ARM®, Thumb® are the registered trademarks of ARM, Ltd.; Other terms and product names may be the trademarks of others.



Printed on recycled paper.