

NPN SILICON RF TRANSISTOR NE661M04

NPN SILICON RF TRANSISTOR FOR LOW CURRENT, LOW NOISE, HIGH-GAIN AMPLIFICATION FLAT-LEAD 4-PIN THIN SUPER MINI-MOLD

FEATURES

- Low noise and high gain with low collector current
- $NF = 1.2 \text{ dB}$, $G_a = 16 \text{ dB TYP.}$ @ $f = 2 \text{ GHz}$, $V_{CE} = 2 \text{ V}$, $I_c = 2 \text{ mA}$
- Maximum stable power gain: $MSG = 22 \text{ dB TYP.}$ @ $f = 2 \text{ GHz}$, $V_{CE} = 2 \text{ V}$, $I_c = 5 \text{ mA}$
- $f_r = 25 \text{ GHz}$ technology
- Flat-lead 4-pin thin super mini-mold ($t = 0.59 \text{ mm}$)

ORDERING INFORMATION

Part Number	Quantity	Packaging Style
NE661M04	Loose product (50 pcs)	<ul style="list-style-type: none"> • 8 mm wide emboss taping • 1 pin (emitter), 2 pin (collector) feed hole direction
NE661M04-T2	Taping product (3 kpcs/reel)	

Remark To order evaluation samples, consult your NEC sales representative (available in 50-pcs units).

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	V_{CBO}	15	V
Collector to Emitter Voltage	V_{CEO}	3.3	V
Emitter to Base Voltage	V_{EBO}	1.5	V
Collector Current	I_c	12	mA
Total Power Dissipation	P_{tot}^{Note}	39	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-65 to +150	°C

Note $T_A = +25^\circ\text{C}$ (free air)

THERMAL RESISTANCE

Item	Symbol	Value	Unit
Junction to Case Resistance	R_{th-j-c}	240	°C/W
Junction to Ambient Resistance	R_{th-j-a}	650	°C/W

Because this product uses high-frequency technology, avoid excessive static electricity, etc.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.

Not all devices/types available in every country. Please check with local NEC representative for availability and additional information.

ELECTRICAL CHARACTERISTICS (T_A = +25°C)

Parameter	Symbol	Test Conditions	MIN.	TYP.	MAX.	Unit
DC characteristics						
Collector Cut-off Current	I _{CBO}	V _{CB} = 5 V, I _E = 0	–	–	100	nA
Emitter Cut-off Current	I _{EBO}	V _{EB} = 1 V, I _C = 0	–	–	100	nA
DC Current Gain	h _{FE} ^{Note 1}	V _{CE} = 2 V, I _C = 5 mA	50	70	100	–
RF Characteristics						
Reverse Transfer Capacitance	C _{re} ^{Note 2}	V _{CB} = 2 V, I _E = 0, f = 1 MHz	–	0.08	0.12	pF
Gain Bandwidth Product	f _T	V _{CE} = 3 V, I _C = 10 mA, f = 2 GHz	20	25	–	GHz
Noise Figure	NF	V _{CE} = 2 V, I _C = 2 mA, f = 2 GHz, Z _S = Z _{opt}	–	1.2	1.5	dB
Insertion Power Gain	S _{21e} ²	V _{CE} = 2 V, I _C = 5 mA, f = 2 GHz	14	17	–	dB
Maximum Stable Power Gain	MSG ^{Note 3}	V _{CE} = 2 V, I _C = 5 mA, f = 2 GHz	–	22	–	dB
Output Power at 1 dB Compression Point	P ₋₁	V _{CE} = 2 V, I _C = 5 mA ^{Note 4} , f = 2 GHz	–	5	–	dBm
Output Power at Third Order Intercept Point	OIP ₃	V _{CE} = 2 V, I _C = 5 mA ^{Note 4} , f = 2 GHz	–	15	–	–





- Notes**
1. Pulse measurement PW ≤ 350 μs, Duty cycle ≤ 2%
 2. Emitter to base capacitance measured using capacitance meter (self-balancing bridge method) when the emitter is connected to the guard pin
 3. $MSG = \left| \frac{S_{21}}{S_{12}} \right|$
 4. Collector current when P₋₁ is output

h_{FE} CLASSIFICATION



Rank	FB
Marking	T78
h _{FE}	50 to 100

TYPICAL CHARACTERISTICS (T_A = +25°C)




Thermal/DC Characteristics





Capacitance/f_T Characteristics







Gain Characteristics



Output Characteristics



Noise Characteristics



S PARAMETER

$V_{CE} = 2\text{ V}$, $I_c = 2\text{ mA}$

Frequency GHz	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.90	-3.7	6.45	174.8	0.00	81.9	0.98	-3.6
0.2	0.89	-7.1	6.25	170.8	0.01	77.9	0.95	-6.0
0.3	0.89	-10.6	6.12	167.2	0.01	75.5	0.94	-7.9
0.4	0.88	-14.2	6.02	163.6	0.02	75.7	0.92	-9.5
0.5	0.87	-17.6	5.96	160.2	0.02	74.1	0.91	-11.0
0.6	0.87	-21.0	5.87	156.9	0.02	72.4	0.90	-12.7
0.7	0.86	-24.6	5.79	153.4	0.03	70.0	0.89	-14.3
0.8	0.84	-28.0	5.69	150.3	0.03	68.7	0.88	-15.6
0.9	0.83	-31.5	5.64	147.1	0.03	66.9	0.87	-17.3
1.0	0.82	-35.0	5.54	143.8	0.03	65.2	0.86	-18.9
1.1	0.80	-38.6	5.50	140.7	0.04	63.3	0.84	-20.3
1.2	0.79	-42.0	5.42	137.7	0.04	62.2	0.83	-21.8
1.3	0.77	-45.8	5.37	134.5	0.04	60.1	0.82	-23.3
1.4	0.76	-49.4	5.28	131.6	0.04	58.4	0.81	-24.9
1.5	0.74	-53.4	5.25	128.5	0.05	57.0	0.80	-26.4
1.6	0.72	-57.1	5.19	125.2	0.05	55.0	0.78	-27.8
1.7	0.70	-61.0	5.14	122.4	0.05	53.1	0.77	-29.3
1.8	0.68	-65.0	5.06	119.2	0.05	52.1	0.76	-30.7
1.9	0.66	-69.2	5.04	116.1	0.06	50.9	0.75	-32.2
2.0	0.64	-73.3	4.98	113.0	0.06	49.1	0.73	-33.6
2.1	0.62	-77.7	4.91	109.9	0.06	46.6	0.72	-35.1
2.2	0.60	-82.1	4.82	106.9	0.06	45.6	0.71	-36.3
2.3	0.58	-86.9	4.78	103.6	0.06	43.8	0.69	-37.8
2.4	0.56	-91.8	4.68	100.6	0.06	42.2	0.68	-39.2
2.5	0.55	-97.1	4.62	97.5	0.07	40.5	0.66	-40.5
2.6	0.52	-102.5	4.53	94.1	0.07	39.0	0.65	-41.9
2.7	0.50	-108.7	4.46	90.8	0.07	37.0	0.63	-43.0
2.8	0.47	-115.5	4.29	87.5	0.07	34.8	0.62	-44.1
2.9	0.42	-120.2	4.11	85.2	0.06	34.7	0.61	-44.0
3.0	0.40	-119.0	4.06	84.6	0.06	38.1	0.61	-45.4
4.0	0.47	-159.3	3.24	66.5	0.07	33.4	0.51	-55.3
5.0	0.49	163.9	2.74	45.5	0.07	33.5	0.44	-69.8
6.0	0.56	141.2	2.34	26.7	0.08	35.9	0.40	-88.9
7.0	0.63	123.9	2.00	9.3	0.09	37.0	0.38	-112.9
8.0	0.69	111.6	1.70	-6.5	0.11	35.9	0.39	-138.6
9.0	0.74	102.1	1.44	-21.4	0.12	31.3	0.44	-163.4
10.0	0.79	95.1	1.19	-34.9	0.13	25.3	0.52	175.7


V_{CE} = 2 V, I_c = 5 mA

Frequency GHz	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.	MAG.	ANG.
0.1	0.82	-4.7	10.44	173.8	0.00	80.8	0.97	-4.1
0.2	0.82	-9.2	10.28	168.8	0.01	75.3	0.94	-7.1
0.3	0.80	-13.8	10.09	164.2	0.01	75.0	0.92	-9.4
0.4	0.79	-18.0	9.89	159.8	0.01	74.1	0.90	-11.5
0.5	0.78	-22.4	9.73	155.6	0.02	72.2	0.88	-13.4
0.6	0.76	-26.6	9.55	151.5	0.02	70.4	0.87	-15.4
0.7	0.74	-31.1	9.36	147.4	0.02	68.0	0.85	-17.3
0.8	0.72	-35.3	9.19	143.5	0.03	66.6	0.84	-18.9
0.9	0.70	-39.4	9.01	139.6	0.03	64.9	0.82	-20.8
1.0	0.68	-43.6	8.82	135.8	0.03	63.3	0.80	-22.4
1.1	0.66	-47.9	8.67	132.0	0.03	61.2	0.78	-23.9
1.2	0.63	-51.9	8.46	128.6	0.04	60.7	0.77	-25.5
1.3	0.61	-56.2	8.27	124.8	0.04	58.7	0.75	-26.9
1.4	0.58	-60.3	8.07	121.5	0.04	57.8	0.73	-28.4
1.5	0.56	-64.7	7.91	117.9	0.04	56.3	0.72	-29.7
1.6	0.53	-68.9	7.72	114.5	0.04	55.5	0.70	-31.0
1.7	0.51	-73.3	7.54	111.3	0.05	53.8	0.69	-32.3
1.8	0.49	-77.6	7.35	108.2	0.05	53.4	0.67	-33.6
1.9	0.46	-82.0	7.18	105.0	0.05	51.9	0.65	-34.9
2.0	0.44	-86.7	7.00	102.0	0.05	51.6	0.64	-36.1
2.1	0.42	-91.6	6.83	98.9	0.05	49.6	0.62	-37.2
2.2	0.40	-96.5	6.66	95.9	0.05	49.6	0.61	-38.2
2.3	0.38	-101.9	6.49	92.9	0.05	48.3	0.60	-39.5
2.4	0.36	-107.6	6.32	90.0	0.05	47.4	0.58	-40.5
2.5	0.35	-113.6	6.16	87.0	0.06	46.2	0.57	-41.7
2.6	0.33	-120.2	6.00	84.1	0.06	45.3	0.55	-42.7
2.7	0.32	-127.9	5.82	80.9	0.06	44.6	0.53	-43.4
2.8	0.30	-137.3	5.59	77.9	0.06	42.5	0.52	-43.8
2.9	0.25	-144.7	5.29	76.3	0.06	44.1	0.52	-43.2
3.0	0.23	-142.4	5.22	76.0	0.06	48.2	0.52	-44.8
4.0	0.31	175.3	4.23	62.3	0.06	46.8	0.44	-48.3
5.0	0.42	147.1	3.50	41.8	0.08	45.6	0.36	-70.4
6.0	0.51	130.2	2.94	25.6	0.09	42.7	0.31	-89.6
7.0	0.58	116.8	2.52	9.8	0.10	38.6	0.29	-115.3
8.0	0.65	106.9	2.16	-5.0	0.12	34.4	0.31	-143.0
9.0	0.71	99.0	1.85	-19.3	0.13	28.7	0.36	-168.2
10.0	0.76	92.8	1.57	-32.6	0.14	22.9	0.44	172.1
11.0	0.78	89.2	1.36	-44.5	0.14	17.8	0.53	158.5
12.0	0.79	84.8	1.16	-55.1	0.15	13.4	0.60	149.8


NOISE PARAMETER

<Equal NF circle>

$V_{CE} = 2\text{ V}$
 $I_C = 2\text{ mA}$
 $f = 2\text{ GHz}$



$V_{CE} = 2\text{ V}$
 $I_C = 2\text{ mA}$
 $f = 1\text{ GHz}$



$V_{CE} = 2\text{ V}, I_C = 2\text{ mA}$



f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		R _n /50
			MAG.	ANG.	
0.8	0.93	22.9	0.54	13.3	0.47
0.9	0.95	22.2	0.54	14.9	0.47
1.0	0.97	21.6	0.54	16.4	0.47
1.5	1.08	18.8	0.53	24.6	0.45
1.8	1.14	17.5	0.51	30.3	0.43
1.9	1.16	17.1	0.50	32.4	0.42
2.0	1.18	16.7	0.49	34.6	0.41
2.5	1.29	15.2	0.44	47.7	0.35

$V_{CE} = 2\text{ V}, I_C = 5\text{ mA}$

f (GHz)	NF _{min} (dB)	G _a (dB)	Γ _{opt}		R _n /50
			MAG.	ANG.	
0.8	1.59	24.7	0.38	10.7	0.43
0.9	1.60	24.1	0.38	11.9	0.43
1.0	1.60	23.4	0.38	13.2	0.43
1.5	1.62	20.7	0.36	20.5	0.41
1.8	1.63	19.3	0.34	25.7	0.38
1.9	1.63	18.9	0.33	27.5	0.38
2.0	1.63	18.5	0.32	29.4	0.37
2.5	1.65	16.9	0.26	40.1	0.32

PACKAGE DRAWINGS

Flat-lead 4-pin thin super mini-mold (unit: mm)



Pin connections

- 1. Emitter
- 2. Collector
- 3. Emitter
- 4. Base

SOLDERING CONDITIONS

Solder this product under the following recommended conditions.

For soldering methods and conditions other than those recommended, consult NEC.

Soldering Method(s)	Soldering Conditions	Recommended Conditions Symbol
Infrared reflow	Package peak temperature: 235°C, Time: 30 sec max. (210°C min.), Number of times: twice max., Maximum number of days: None ^{Note}	IR35-00-2
VPS	Package peak temperature: 215°C, Time: 40 sec max. (200°C min.), Number of times: twice max., Maximum number of days: None ^{Note}	VP15-00-2
Wave soldering	Solder bath temperature: 260°C, Time: 10 sec max., Number of times: once, Maximum number of days: None ^{Note}	WS60-00-1

Note Number of days in storage after the dry pack has been opened. The storage conditions are at 25°C, 65% RH MAX.

Caution Do not use two or more soldering methods in combination.

For details of the recommended soldering conditions, refer to information document **Semiconductor Device Mounting Technology Manual (C10535E)**.

[MEMO]

- **The information in this document is current as of June, 2000. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC's data sheets or data books, etc., for the most up-to-date specifications of NEC semiconductor products. Not all products and/or types are available in every country. Please check with an NEC sales representative for availability and additional information.**
 - No part of this document may be copied or reproduced in any form or by any means without prior written consent of NEC. NEC assumes no responsibility for any errors that may appear in this document.
 - NEC does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC semiconductor products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC or others.
 - Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of customer's equipment shall be done under the full responsibility of customer. NEC assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
 - While NEC endeavours to enhance the quality, reliability and safety of NEC semiconductor products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC semiconductor products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment, and anti-failure features.
 - NEC semiconductor products are classified into the following three quality grades:
"Standard", "Special" and "Specific". The "Specific" quality grade applies only to semiconductor products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of a semiconductor product depend on its quality grade, as indicated below. Customers must check the quality grade of each semiconductor product before using it in a particular application.
"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.
- The quality grade of NEC semiconductor products is "Standard" unless otherwise expressly specified in NEC's data sheets or data books, etc. If customers wish to use NEC semiconductor products in applications not intended by NEC, they must contact an NEC sales representative in advance to determine NEC's willingness to support a given application.
- (Note)
- (1) "NEC" as used in this statement means NEC Corporation and also includes its majority-owned subsidiaries.
 - (2) "NEC semiconductor products" means any semiconductor product developed or manufactured by or for NEC (as defined above).