

PRODUCT BRIEF (S3C89K8)

High Performance and Low Power Consumption contact/contactless Smart Card Microcontroller

The S3C89K8 single-chip CMOS microcontroller is specially designed and packaged for "contact/contact less smart card" application. The SAM87RC 8-Bit CPU architecture supports Stop and Idle power-down modes to reduce power consumption. The S3C89K8 has SAM87RC 8-Bit CPU, 24K bytes of program memory (ROM), 8K bytes of program/data memory (EEPROM), 272-byte general-purpose register file and 512-byte static RAM.

HARDWARE FEATURES

CPU

- SAM87RC 8-bit CPU core
- 78 instructions, including multiply and divide
- STOP and IDLE instructions added to reduce power consumption

Memory

- 24K bytes of ROM for program memory
- 8K bytes of EEPROM for program/data memory
- 512 bytes static RAM for program/data memory
- 272 bytes for general-purpose register file

EEPROM Write Operations

- Programmable EEPROM erase/write time
- Byte-wise to page-wise (32 bytes) EEPROM erase/write operations are supported
- 1,000,000 erase/write cycles
- 100 years data retention

Data Security

- Invisible ROM code due to implantation
- 32 bytes security PROM, hardware protected
- 32 bytes non erasable EEPROM
- Unique serial number for each chip
- Reset operations are selective if abnormal voltage/frequency/temperature/light exposure/decapsulation is detected.

Interrupts

- Two interrupt sources and vectors

RESET

- Power-on reset circuit
- External reset circuit

DES (Data Encryption Standard)

- Built-in triple DES logic
- Encryption / Decryption
- Start and Stop control

16-bit Random Number Generator

- One 16-bit random number generator with internal ring oscillator
- Start and stop control

Automatic Operating Mode Detect

- Contact/Contactless

Contactless Specific Features

- 13.56 MHz operation
- 106 Kbps or higher data transfer rate
- 10% or 100% ASK demodulation
- Load modulation
- Programmable RF interface parameters
- ISO14443 (type B)

Contact Specific Features

- Operating voltage: 2.7 - 5.5 V
- ISO 7816-3 compatible
- Operating frequency: 1 - 5 MHz


Operating Temperature

- -25 °C to +85 °C

Package

- Wafer
- 8-pin COB (conforms to ISO standard 7816)

S3C89K8 Block Diagram



Electrical Characteristics

- Supply voltage: -0.3 to $+7.0$ V
- Operating temperature: -25 °C to $+85$ °C
- Operating voltage: 2.7 – 5.5 V
- Supply current :
 - contact (@3.57MHz, 5V) 3.5mA(typical)
 - contactless(@3.57MHz, 3V) 1mA(typical)
- Stop current(5V) :0.5mA(typical)

Development Tools

- In-Circuit Emulator: OPENice-i500
- C Compiler: IAR C-Compiler
- Simulator
- Emulation Board

For More Information

Samsung Electronics Co., Ltd
Suwon P.O.Box 105
Kyunggi-Do, KOREA, 440-600
TEL: 82-31-209-5237
FAX: 82-31-209-6494
Email:chipcard@samsung.co.kr