

# SHINDENGEN

## General Purpose Rectifiers

SIL Bridges

**D2SB20**

**200V 1.5A**

### FEATURES

- Thin Single In-Line Package
- High IFSM
- Applicable to Automatic Insertion


### APPLICATION

- Switching power supply
- Home Appliances, Office Equipment
- Telecommunication, Factory Automation

### OUTLINE DIMENSIONS

Case : 2S

Unit : mm



### RATINGS

Absolute Maximum Ratings (If not specified TI=25 )


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-40 ~ 150	
Operating Junction Temperature	Tj		150	
Maximum Reverse Voltage	V <sub>RM</sub>		200	V
Average Rectified Forward Current	I <sub>O</sub>	50Hz sine wave, R-load, On glass-epoxy substrate, Ta=25	1.5	A
Peak Surge Forward Current	I <sub>FSM</sub>	50Hz sine wave, Non-repetitive 1cycle peak value, Tj=25	80	A
Current Squared Time	I <sup>2</sup> t	2ms t < 10ms Tj=25	32	A <sup>2</sup> s


Electrical Characteristics (If not specified TI=25 )

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =0.75A, Pulse measurement, Rating of per diode	Max.1.05	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =V <sub>RM</sub> , Pulse measurement, Rating of per diode	Max.10	$\mu$ A
Thermal Resistance	j <sub>L</sub>	junction to lead	Max.10	/W
	j <sub>A</sub>	junction to ambient	Max.47	


# D2SBx

## Forward Voltage





$T_j = 150^\circ\text{C}$   
Sine wave



Sine wave  
R-load  
Free in air

# D2SBx

## Peak Surge Forward Capability

