MATERIAL SAFETY 3M

DATA SHEET 3M Center

St. Paul, Minnesota

55144-1000

1-800-364-3577 or (651) 737-6501 (24 hours)

Copyright, 2001, Minnesota Mining and Manufacturing Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that:

- 1) the information is copied in full with no changes unless prior agreement is obtained from 3M, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

DIVISION: ELECTRICAL PRODUCTS DIVISION

TRADE NAME:

SFTW SERIES HEAT SHRINK TUBING

ISSUED: June 20, 2001

SUPERSEDES: February 02, 2001

DOCUMENT: 06-6555-4

1. INGREDIENT	C.A.S. NO.	
FLAME RETARDANT POLYOLEFIN	Unknown	100
2. PHYSICAL DATA		
BOILING POINT: N/A VAPOR PRESSURE: N/A VAPOR DENSITY: N/A EVAPORATION RATE: N/A SOLUBILITY IN WATER: N/A SPECIFIC GRAVITY: 1.3 Water: PERCENT VOLATILE: N/A pH: N/A VISCOSITY: N/A MELTING POINT: N/D  APPEARANCE AND ODOR: Black tubing, various sizes, odorless	=1	
3. FIRE AND EXPLOSION HAZARD DATA		
FLASH POINT:		

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

June 20, 2001 PAGE 2

\_\_\_\_\_

# 3. FIRE AND EXPLOSION HAZARD DATA (continued)

------

### EXTINGUISHING MEDIA:

Carbon dioxide, Dry chemical, Foam

### SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

NFPA HAZARD CODES: HEALTH: 1 FIRE: 1 REACTIVITY: 0

UNUSUAL REACTION HAZARD: none

OSHA FIRE HAZARD CLASS: Not applicable

\_\_\_\_\_

### 4. REACTIVITY DATA

-----

STABILITY: Stable

INCOMPATIBILITY - MATERIALS/CONDITIONS TO AVOID:

None known.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur.

## HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Aldehydes, Oxides of Antimony, Toxic Vapors, Gases or Particulates

Heating product beyond temperature recommended by instruction sheet may cause release of the following compounds: Benzene, Toluene, Formaldehyde, Acetaldehyde, and Hydrogen Bromide.

-----

# 5. ENVIRONMENTAL INFORMATION

-----

SPILL RESPONSE:

Not applicable.

RECOMMENDED DISPOSAL:

Dispose of waste product in a sanitary landfill.

ENVIRONMENTAL DATA:

No data available.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

June 20, 2001 PAGE 3

\_\_\_\_\_

### 5. ENVIRONMENTAL INFORMATION (continued)

\_\_\_\_\_\_

## REGULATORY INFORMATION:

Volatile Organic Compounds: N/A. VOC Less H2O & Exempt Solvents: N/A.

Since regulations vary, consult applicable regulations or authorities before disposal.

## EPCRA HAZARD CLASS:

FIRE HAZARD: NO PRESSURE: NO REACTIVITY: NO ACUTE: NO CHRONIC: NO

\_\_\_\_\_

#### 6. SUGGESTED FIRST AID

------

### EYE CONTACT:

If exposed to vapors or smoke, immediately flush eyes with large amounts of water. Get immediate medical attention.

### SKIN CONTACT:

If skin contact with hot material occurs: DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Immediately flush affected area with plenty of cold water and cover with a clean dressing. Have burn treated by a physician.

## INHALATION:

If signs/symptoms occur, remove person to fresh air. If signs/symptoms continue, call a physician.

## IF SWALLOWED:

Drink two glasses of water. Call a physician.

\_\_\_\_\_

# 7. PRECAUTIONARY INFORMATION

-----

# EYE PROTECTION:

Avoid eye contact with vapors or smoke resulting from overheating or when used in confined areas.

# SKIN PROTECTION:

Avoid skin contact with hot material. Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns.

# RECOMMENDED VENTILATION:

Local exhaust is required for operations using large amounts of material. Conduct air monitoring to determine adequacy of ventilation. Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

MSDS: SFTW SERIES HEAT SHRINK TUBING June 20, 2001

PAGE 4

\_\_\_\_\_\_ 7. PRECAUTIONARY INFORMATION (continued)

\_\_\_\_\_\_

WHEN USING THIS PRODUCT IN A CONFINED SPACE OR WHERE VENTILATION MAY BE INADEQUATE THEN RESPIRATORY PROTECTION MAY BE WORN. INADEQUATE VENTILATION OR CONFINED SPACES WOULD CAUSE VAPORS FROM HEATING OF THIS PRODUCT TO BE PRESENT IN THE USER'S BREATHING ZONE AND MAY CAUSE RESPIRATORY IRRITATION. EXCESSIVE HEATING OF THIS PRODUCT BEYOND THE RECOMMENDED APPLICATION TEMPERATURE OF 212 DEGREES FAHRENHEIT IS NOT RECOMMENDED AND MAY RESULT IN THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS WHICH MAY RESULT IN ADVERSE HEALTH EFFECTS.

#### RESPIRATORY PROTECTION:

Avoid breathing of fumes. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half-mask organic vapor respirator with dust/mist prefilter.

PREVENTION OF ACCIDENTAL INGESTION:

Wash hands after handling and before eating.

# RECOMMENDED STORAGE:

Store at room temperature. Keep out of the reach of children.

FIRE AND EXPLOSION AVOIDANCE:

Not applicable.

HMIS HAZARD RATINGS: HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTION: B

## EXPOSURE LIMITS

INGREDIENT		VALUE	UNIT	TYPE	AUTH	SKIN*
FLAME RETARDANT	POLYOLEFIN	NONE	NONE	NONE	NONE	

\* SKIN NOTATION: Listed substances indicated with 'Y' under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

SOURCE OF EXPOSURE LIMIT DATA:

- NONE: None Established

June 20, 2001 PAGE 5

\_\_\_\_\_

#### 8. HEALTH HAZARD DATA

-----

#### EYE CONTACT:

Vapors from heated material may cause eye irritation.

#### SKIN CONTACT:

Skin Burns (thermal, from contact with hot material): signs/symptoms can include burning pain, red and swollen skin, and blisters.

### INHALATION:

Vapors of heated material may cause respiratory system irritation.

RESPIRATORY IRRITATION WOULD NOT BE EXPECTED IN APPLICATIONS WHERE ADEQUATE VENTILATION AND PROPER APPLICATION (AT DESIGNATED TEMPERATURES) IS UTILIZED. EXCESSIVE HEATING AND INADEQUATE VENTILATION MAY RESULT IN EXPOSURE TO THERMAL DEGRADATION AND DECOMPOSITION PRODUCTS AS INDICATED IN SECTION 4 OF THIS MSDS UNDER "REACTIVITY DATA-HAZARDOUS DECOMPOSITION PRODUCTS".

# IF SWALLOWED:

Ingestion is not a likely route of exposure to this product.

\_\_\_\_\_

### SECTION CHANGE DATES

\_\_\_\_\_\_

HEADING SECTION CHANGED SINCE February 02, 2001 ISSUE FIRE AND EXPL. SECTION CHANGED SINCE February 02, 2001 ISSUE

-----

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

\_\_\_\_\_\_

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.