





| | |
|--|---|
| <p>POS. 1</p>  <p>2x JACKSCREW 4-40 UNC with allen wrench head</p> | <p>POS. 2</p>  <p>1x CABLE STRAIN RELIEF</p> |
| <p>POS. 3</p>  <p>2x COVER SCREW</p> | <p>POS. 4</p>  <p>2x CABLE STRAIN RELIEF SCREW</p> |

NOTES:

1. HOOD: PBT GF UL 94 V0
2. JACKSCREW 4-40 UNC: STEEL; NICKEL PLATED
3. SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
4. COVER SCREW: STEEL; NICKEL PLATED
5. STRAIN RELIEF: STEEL; NICKEL PLATED
6. FEMALE CONNECTOR 7W2, WITHOUT CONTACTS

Directive 2002/95/EC
„RoHS“
Compliant

| | |
|---|--------|
| APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL | |
| CUSTOMER APPROVAL DATE: | |
| NAME: | TITLE: |
| COMPANY NAME: | |
| APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL | |

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

| | | | | | | | | | |
|-----------|-------------|------|--------------|--------------|--|--|--|--|--|
| | | | | | | | | | |
| tolerance | ISO 2768-m | | dim. in mm | | | | | | |
| date | 17.12.07 | name | Schmidt | | | | | | |
| appd. | 17.12.07 | name | Mickenbecker | | | | | | |
| norm | | | | | | | | | |
| d-old | | | | | | | | | |
| a | Origin | | | | | | | | |
| rev. | description | date | name | CONEC | | | | | |

| | |
|--|--------|
| scale: 2:1 | |
| material: see notes | |
| title: PLASTIC HOOD with 7W2 Female Crimp Connector straight cable exit | |
| dwg no: Inventor 10 | DIN-A3 |
| 13K3A2364 | |
| part no: 13-000370 | sh: 1 |