





**Mechanical Dimensions**

All dimensions are in millimeters (inches)



A vertical float switch, with either normally open or normally closed (when the float is down) switching action, permanently coupled to a 300mm PVC tube. This provides a float switch, whose overall depth can be varied between 150mm and 450mm, by adjusting its position in a sliding clamp.

Further 306mm PVC extension tubes may be added, up to a maximum of three, to provide insertion depths up to 1350mm.

- **Insertion Depth 150mm - 350mm**
- **Easy to install**
- **Adjustable Level**

**Technical Specification**

Operating Temperature	°C	0 / +75
	°F	32/+167
Minimum S.G. of Fluid		0.65
Float material		Polypropylene
Stem material		Polyphenylene Sulphide
Tube material		PVC Class 7
Cable length Metres		1.5
Maximum Switching Voltage	(V ac/dc)	250/120
Maximum Switching Current	(A)	0.5
Maximum Switching Power	(W/VA)	25

All ratings are for resistive load only

**Electrical Specification**

Contact Form	N/O (N/C)
Switching Power Max. VA	25
Switching Voltage AC Max.	240
Switching Voltage DC Max.	120
Switching Current Max. A	0.6



**USA**

Cynergy3 Components  
2320 Paseo de las Americas, Suite 104  
San Diego, CA 92154

Sales & Tech Support (866) 258-5057  
Email: sales@cynergy3.com

**EUROPE - UK**

Cynergy3 Components Ltd.  
7 Cobham Road  
Ferndown Industrial Estate  
Wimborne, Dorset BH21 7PE

Telephone +44 (0) 1202 897969  
Fax +44 (0) 1202 891918  
Email:sales@cynergy3.com