

Product SKU: C1363.38.90
Product Description: Speaker Wire, UL Listed (Wires, Misc.) 120V max., No. of Conductors: 2, Gauge Size (AWG): 12, Conductor/Strands: 65/30, Jacket: Premium Grade PVC - Clear - 500 Ft. Reel
Product Category: Electronics - Special Applications - Audio, Video, and Entertainment Cable - Speaker Wire - Clear



Product Construction:

- Conductor: • 24 thru 12 AWG fully-annealed 1 bare, 1 tin stranded copper per ASTM B-174
- Insulation/Jacket: • Premium grade PVC

Product Specification:

- No. of Conductors: • 2
- Conductor Size (AWG): • 12
- Conductor/Strands: • 65/30
- Jacket Color: • Clear
- Nominal Insulation Thickness (in): • 0.030
- Nominal Insulation Thickness (mm): • 0.76
- Nominal Outside Diameter (in): • 0.160 x 0.335
- Nominal Outside Diameter (mm): • 4.06 x 8.51
- Standard Packaging: • 500' Non-returnable Wood Reels
- Standard Package Quantity: • 1
- UPC #: • 079407762576

- Put-up: • 500
- SCC-14: • 50079407762577
- Cube: • 1494.425
- Weight Per Unit of Measure: • .06
- ColorOption: • Clear

Product Information:

- Applications:
- Hi-fi and stereo speaker wire
 - Juke boxes
 - Lamps
 - Radios
 - Suggested voltage rating: 120 Volts
 - Not for in-wall use
- Compliances:
- UL Wires Misc. (UL: 120V)
- Packaging:
- 1000' (305 m) Spools
 - 500' (152 m) Spools
 - Other put-ups available- consult Customer Service

Technical Specifications

[4' Carol Brand Electrical Wire Center](#)

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**