

Product SKU: C2107.41.08

Product Description: Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 10, Conductor/Strands: 105/30, Jacket:

Premium Grade PVC, Temperature Range: -20°C to +105°C - Brown - 1000 Ft. Reel

Product Category: Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Brown



Product Construction:

Conductor: • 24 thru 10 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 10

Conductor/Strands: • 105/30

No. of Pairs: • 1

Jacket Color:

• Brown

Nominal Insulation Thickness • 0.032 (in):

Nominal Insulation Thickness • 0.81 (mm):

Nominal Outside Diameter (in): • 0.184

Nominal Outside Diameter • 4.67 (mm):

Standard Packaging: • 1000' Non-returnable Wood Reels

• 1
• 079407769261
• 1000
• 50079407769266
• 3976.2
• .05
• Brown
Internal wiring of electrical and electronic equipment
• Internal wiring of panels and meters
Point-to-point wiring
• Suggested voltage rating: 600 Volts
• CSA Type TEW
 Designed to Meet UL VW-1 Vertical Wire Flame Test
• UL Style 1015 - 105°C, 600V
• 10,000 foot (3048m) Reels
• 1000' (305 m) Spools
Other put-ups available- consult Customer Service

Conduit Capacity Chart

<u>Cable Design Equations - Coaxial Cable</u> <u>Engineering Prefixes</u> <u>Coax Connector Cross Reference</u>



Glossary



Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

