

Product SKU: C2107.41.10

Product Description: Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 10, Conductor/Strands: 105/30, Jacket:

Premium Grade PVC, Temperature Range: -20°C to +105°C - Gray - 1000 Ft. Reel

Product Category: Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Gray



Product Construction:

Conductor: • 24 thru 10 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 10

Conductor/Strands: • 105/30

No. of Pairs: • 1

Jacket Color: • Gray

Nominal Insulation Thickness • 0.032 (in):

Nominal Insulation Thickness • 0.81 (mm):

Nominal Outside Diameter (in): • 0.184

Nominal Outside Diameter • 4.67 (mm):

Standard Packaging: • 1000' Non-returnable Wood Reels

Standard Package Quantity:	• 1
UPC #:	• 079407002603
Put-up:	• 1000
Cube:	• 480
Weight Per Unit of Measure:	• .0413
ColorOption:	• Gray
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	Other put-ups available- consult Customer Service
Reference Charts	
Color Code Chart	
Technical Specifications	
Unit Conversion Factors	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties Temperature Conversion Chart	
Temperature Conversion Chart Decimal and Unit Conversion Factors	
Cable Design Equations - Braid Shield	
AWG Conductor Chart	
Conduit Capacity Chart	
Cable Design Equations - Coaxial Cable	
Engineering Prefixes	
Coax Connector Cross Reference	





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

