


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF24438-24B	WHITE 10,000°k x = .283 y = .299	1400 TYP. @ 0°C 1820 MAX.	835	5.0		30,000+
				6.5±5%	38,000±10%	

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<div>METRIC</div> <div></div> <div>THIRD ANGLE PROJECTION</div>	<div>DIMENSIONS ARE IN MILLIMETERS</div> <div>TOLERANCE UNLESS OTHERWISE SPECIFIED</div> <div>1 PL +/- 1.0</div> <div>2 PL +/- 0.05</div> <div>ANGLE +/- 0</div>		<div>JKL COMPONENTS CORPORATION</div>				
				TITLE						
			MINIATURE COLD CATHODE FLUORESCENT LAMP							
A ADD DIMENSIONS & ELECTRICAL			DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.		
RELEASED AND CANCEL P-0202-15			L. WENGSTROM	F.D.	3/22/02	A	55335	BF24438-24B		
			- CAD DRAWING -			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
			MANUAL REVISIONS NOT PERMITTED			NONE	3/21/02	3/22/02	A	1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE							