



**NOTES:**

1. MAXIMUM RATING: 20 AMPS
2. BODY MATERIAL: ALCRYN, BLACK  
COVER MATERIAL: ALCRYN, BLACK

**INSPECTION NOTE:**

1. CHECK FOR CIRCUIT CONTINUITY USING FUSE OR COPPER DUMMY.

NO		COMPONENT NO	DESCRIPTION	QTY/M	U/M
<b>BILL OF MATERIAL</b>					
MATERIAL SPEC		FINISH			
COPIES TO	DATE	PJM	SCALE	FULL	
1 9 18	12/14/00				
2 10 19			SUPER DRW		
3 12 20					
4 13 21			RAW STK WT	LBS/M	
5 14 23					
6 15 33	TOLERANCE UNLESS OTHERWISE SPECIFIED				
7 16 43	TWO PLACE DEC ±.01				
8 17 53	THREE PLACE DEC ±.005 ANGULAR ±1°				
<b>TITLE</b>					
ATO IN-LINE FUSEHOLDER					
LTR		REVISION		CHK	APD
E	80834D-REVISE & REDRAW IN NEW FORMAT 12/14/00 PJM				
DESIGNER		DRAWN		FINAL	
Littefuse		E		FHAC0001Z	
DES PLAINES, ILLINOIS 60018					

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CRITICAL CHARACTERISTICS.

CPK DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE

DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF THE TIGHTNESS OF TOLERANCE AND THE PROCEDURE FOR MEASUREMENT. THE TIGHTNESS OF TOLERANCE AND THE PROCEDURE FOR MEASUREMENT ARE LISTED IN THE TOLERANCE AND MEASUREMENT INSTRUCTIONS.

CPK DENOTES CP DIMENSIONS - MINIMUM CP VALUE (CPK) SHALL BE WITHIN THE DIMENSIONAL LIMITATIONS AND TOLERANCES FOR MAXIMUM TOOL LIFE.

