

► General data



Screw-type socket strip, type F, 32-position, equipped in rows z + d, one 1.5 mm² screw connection per position

Order number	2285195
Type	SFL 1,5/F32/ZD
<hr/>	
Barcode number	4017918055882
Unit pack	10 Piece
Customs tariff	85369010000

► Technical data

Dimensions / positions

Length	14.8 mm
Height	37.7 mm
Width	95 mm
Number of positions	32
Hole diameter	2.8 mm
Screw thread	M 3
Tightening torque	0.4 Nm

Technical data


Insulating material group	II
Rated surge voltage (III/3)	4 kV
Connection in acc. with standard	IEC/ DIN VDE
Nominal current I_N	4 A
Nominal voltage U_N	250 V
Insulating material	PA-F
Inflammability class acc. to UL 94	HB
Stripping length	10 mm

Connection data

Min. conductor cross section, rigid	0.5 mm ²
Conductor cross section, rigid max.	1.5 mm ²
Conductor cross section flexible min.	0.5 mm ²
Max. conductor cross section, flexible	1.5 mm ²
Min. conductor cross section AWG/kcmil	20
Conductor cross section AWG/kcmil max	16

▸ Drawings

Dimensioned drawing



► Accessories

Item	Designation	Description
Tools		
1205040	SZS 0,6X2,5	Screwdriver, bladed, matches SFL screw socket strips, blade: 0.6 x 2.5 mm

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved