

CLIPFIX 15

Order No.: 3022263

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3022263>

Snap-on end bracket, to be snapped onto NS 15 DIN rail

Commercial data

| | |
|--------------------------|--------------------|
| EAN | 4017918976330 |
| Pack | 50 Pcs. |
| Customs tariff | 39269097 |
| Weight/Piece | 0.00191 KG |
| Catalog page information | Page 508 (CL-2007) |

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General data**

| | |
|------------------------------------|---------|
| Height | 22.6 mm |
| Length | 22 mm |
| Width | 5.2 mm |
| Material | PA |
| Color | gray |
| Inflammability class acc. to UL 94 | V2 |

Accessories

| Item | Designation | Description |
|------|-------------|-------------|
|------|-------------|-------------|

Assembly

| | | |
|---------|---------------------|--|
| 1401682 | NS 15 PERF 2000MM | DIN rail, material: steel, perforated, height 5.5 mm, width 15 mm, length: 2 m |
| 1401695 | NS 15 UNPERF 2000MM | DIN rail, material: Steel, unperforated, height 5.5 mm, width 15 mm, length: 2 m |

General

| | | |
|---------|-----------------------|--|
| 1401608 | NS 15 BLK PERF 2000MM | DIN rail, material: steel, perforated, height 5.5 mm, width 15 mm, length: 2 m |
|---------|-----------------------|--|

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2008 Phoenix Contact
Technical modifications reserved;