TrippLitePowerStrip

Multipleoutletswhereveryouneedthem

RS-0615-F

- 6frontfacingoutlets
- 15ft.cord
- 19"1Urackmount



All-metalhousing

DESCRIPTION

Tripp Lite's RS -0615-F power strip offers 15 amp capacity AC power distribution in a versatile multi -mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under -counterinstallation. Uses only 1 rack space (1U) when installed in any 19 inch rackmeeting EIA standards. Unfiltered electrical pass -through makes RS -0615-Fideal for distributing alternate waveform UPS or generator power in racken closures, network closets and more. Includes 6 front -facing NEMA5 -15 Routlets, 15 ft AC power cord and lighted switch with latchings afety cover prevents risk of accidental turn -off.

PLUG/OUTLETS:Input:NEMA5 -15P/Output:6Front -facingNEMA5 -15R

ELECTRICAL:120VAC,50/60Hz,15A(RequiresstandardNEMA5 -15Rwallreceptacle)

FORMAT:Supports19in.rackmount(uses1rackspace/1U),wallmount,under -counterandmore

KEYBUYINGPOINTS

- Versatileall -metal cabinet with detachable mounting flanges allows rack mount, wall mount, under counter and other creative mounting options
- Usesonerackspace(1U)instandard19inchrack("zeroU"mountingpossibleinmanyracks)
- Unfilteredelectricalpass -through reliably distributes alternate waveform ACpower from UPS or generator to support edequipment
- 6frontfacingNEMA5 -15Routputreceptacles
- 15footACcordNEMA5 -15Pplugconnection
- Lightedpowerswitchconfirmspoweron/offstatus
- Latchingswitchguardpreventsaccidentalturnoff
- 15ampelectricalcapacitywithcircuitbreaker
- 120VAC,50/60Hzelectricalcompatibility

TYPICALAPPLICATIONS

 Offers multiple outlet power distribution for multiple loads in 19 inch rackmount, wallmount and under internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Idealford is tribution of UPS, generatoror commercially derived AC power to protected equipment.

PACKAGEINCLUDES

- RS-0615-FPowerStrip
- Warrantyinformation
- Instructionmanual

COMPLETESPECIFICATIONS

SYSTEMOVERVIEW	
Systemoverview:	1Urackmount,wallmountorunder -counterinstallablepowerstripwithfrontfacingoutlets
Voltagecompatibility:	120VAC
Frequencycompatibility:	50/60Hz
OUTPUT	
Outputvoltampcapacity(amps):	15A
Outletquantity/type:	6Nema5 -15R
INPUT	
Inputconnectiontype:	Nema5 -15Pinputplug
Inputcordlength(ft.):	15
Inputcordlength(m):	4.572
Recommendedelectricalservice:	15A120V
LEDSALARMS&SWITCHES	
Switches:	Redilluminated2positonswitchcontrolspowertoalloutlets
Lockingswitchcover:	Transparentlockingswitchcoverpreventsaccidentalshutoff
PHYSICAL	
UnitDimensions(HWD/in):	1.75x17.5x4.5
UnitDimensions(HWD/cm):	4.445x44.45x11.4
Materialofconstruction:	Sheetmetal
Formfactorssupported:	1Urackmount,wall -mountandundercounterinstallationsupported
Housingcolor:	Black
Receptaclecolor:	Black
AClinecordcolor:	Black
CERTIFICATIONS	
UL1363(PowerTap):	UL1363(URstatus)
cUL/CSA(Canada):	cUL
NOM(Mexico):	NOM
WARRANTY	
Productwarranty:	Lifetime
SPECIALFEATURES	
TVSSgrounding:	Backpanelnutandboltgroundinglug

ThepolicyofTrippLiteisoneofcontinuousimprovement. Specificationsaresubjecttochangewithoutnotice. Therefore,yourproductmayvaryslightlyfromwhatiscurrentlylisted. Pleasemakenotethatthisinformationwaspostedon08/04/2003.



TrippLiteWorldHeadquarters 1111W.35thStreet Chicago,IL60609USA

> CustomerSupport (773)869 -1234

© 2003TrippLite.AllRightsReserved.