RS-1215

- Designed for standard 19-inch racks (1U high)
- 12 outlets (6 front / 6 rear)
- 15-amp circuit breaker



15 ft. cord

DESCRIPTION

Tripp Lite's RS-1215 Power Strip offers 15 amp capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19 inch rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 NEMA5-15R outlets (6 front / 6 rear), 15 ft AC power cord and lighted switch with cover prevents risk of accidental turn-off.

PLUG / OUTLETS: Input: NEMA 5-15P Output: 12 NEMA5-15R (6 front & 6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: Supports 19 in. rackmount (uses 1 rack space / 1U), wallmount, under-counter and more

KEY BUYING POINTS

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting
 options
- Uses one rack space (1U) in standard 19 inch rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 NEMA5-15R output receptacles (6 front / 6 rear)
- 15 foot AC cord NEMA5-15P plug connection
- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn off
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

TYPICAL APPLICATIONS

 Offers multiple outlet power distribution for multiple loads in 19 inch rackmount, wallmount and under-counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

PACKAGE INCLUDES

- RS-1215
- Mounting hardware
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
System overview:	1U rackmount, wallmount or under-counter installable power strip with front and rear facing outlets
Voltage compatibility:	120VAC
Frequency compatibility:	50/60 Hz
OUTPUT	
Output volt amp capacity (amps):	15A
Outlet quantity / type:	12 Nema 5-15R
Outlet orientation:	6 front facing / 6 rear facing
INPUT	
Input connection type:	Nema 5-15P input plug
Input cord length (ft.):	15
Input cord length (m):	4.572
Recommended electrical service:	15A 120V
LEDS ALARMS & SWITCHES	
Switches:	Red illuminated 2 positon switch controls power to all outlets
Locking switch cover:	Transparent locking switch cover prevents accidental shutoff
PHYSICAL	
Unit Dimensions (HWD/in):	1.75 x 17.5 x 4.5
Unit Dimensions (HWD/cm):	4.445 x 44.45 x 11.4
Material of construction:	Sheet metal
Form factors supported:	1U rackmount, wall-mount and undercounter installation supported
Housing color:	Black
Receptacle color:	Black
AC line cord color:	Black
CERTIFICATIONS	
UL1363 (Power Tap):	UL1363 (UR status)
cUL / CSA (Canada):	cUL
WARRANTY	
Product warranty:	Lifetime
SPECIAL FEATURES	
TVSS grounding:	Back panel nut and bolt grounding lug

The policy of Tripp Lite is one of continuous improvement. Specifications are subject to change without notice. Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.