

DESCRIPTION

Tripp Lite's SS7619-15 six-foot power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 24 NEMA 5-15R output receptacles with 2.795 inch center-tocenter spacing, 15 foot AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15 amp resettable circuit breaker and attractive gray color scheme.

PLUG / OUTLETS: Input: NEMA 5-15P / Output: 24 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: Six foot corded vertical / raceway power distribution strip

SUPPRESSION: 450 joules AC suppression

KEY BUYING POINTS

- Long 6 foot / 72 inch strip offers convenient power distribution and surge suppression in equipment racks, computer rooms, workbenches, raceways and more
- Includes 24 NEMA 5-15R output receptacles with 2.795 inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Adjustable mounting clips support installation in a variety of application types
- UL1363 / 1449 400V (USA), cUL (Canada)
- 15 amp power handling capacity with circuit breaker
- 450 joules AC surge suppression
- 15 foot AC line cord

TYPICAL APPLICATIONS

• Offers multiple outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

PACKAGE INCLUDES

- SS7619-15 Power Strip / Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
Voltage compatibility:	120 VAC
Frequency compatibility:	50/60 Hz
Ουτρυτ	
Output volt amp capacity (amps):	15
Output watt capacity (watts):	1800
Outlet quantity / type:	24 NEMA 5-15R output receptacles
Outlet spacing:	2.795 inch (center to center)
INPUT	
Input connection type:	NEMA 5-15P input plug
Input cord length (ft.):	15
Input cord length (m):	4.6
Input cord gauge, type:	14 gauge, SJT
Recommended electrical service:	120V 15A
LEDS ALARMS & SWITCHES	
Switches:	Lighted two position power switch controls power to all outlets
Locking switch cover:	Transparent locking switch cover prevents accidental shutoff
AC SURGE / NOISE SUPPRESSION	
Protection modes:	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating:	450 joules
UL1499 let through rating:	400V - UL Verified
Immunity:	Conforms to IEE 587 / ANSI C62.41
PHYSICAL	
Unit Dimensions (HWD/in):	1.5 x 1.5 x 72 (6 ft. length)
Unit Dimensions (HWD/cm):	3.8 x 3.8 x 182.9
Material of construction:	Metal
Mounting accessories included:	Included mounting brackets enable vertical or horizontal mounting in rack enclosures, raceways and a variety of other configurations
Housing color:	Gray aluminum housing
Receptacle color:	Black
AC line cord color:	Black
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression):	UL1449
cUL / CSA (Canada):	CUL
cUL / CSA (Canada): WARRANTY	

The policy of Tripp Lite is one of continuous improvement. Specifications are subject to change without notice. Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.