



#### General ordering data

Order No.	1918600000
Part designation	SF 1/21 NEUTRAL RT V2
Version	Conductor markers, L x W: 21 x 3 mm, Polyamide 66, red
EAN	4032248554454

#### Markings

Cadmium	no
Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes
Can be written with dot-matrix printer	No
Can be written with laser printer	No
Conductor O.D., max.	2.1 mm
Conductor O.D., min.	1.7 mm
Conductor cross-section, max.	0.75 mm <sup>2</sup>
Conductor cross-section, min.	0.5 mm <sup>2</sup>
Function	Conductor and cable markers
Halogen	no
Height	3 mm
Insulation cross-section, max.	2.1 mm
Length	21 mm
Material	Polyamide 66
Material colour	red
Material colour according to resistance code	2
Max. temperature, continuous	100 °C
Min. temperature, continuous	-40 °C
Pin can be written (STI)	Yes
PrintJet	Yes
Printed characters	without
Silicone	no
Speed marking laser	Yes
Type of printing	Neutral
UL 94 flammability class	V2
Vibration-proof	as for IEC 68-2-6

### Markings

Width 3 mm

### Approvals

Approvals institutes n.a.

### Classifications

eClass 4.1	24-19-02-19
eClass 5.0	27-14-91-03
eClass 5.1	27-14-91-03

### Similar products

Order No.	Part designation	Version
1918490000	SF 0/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 3 mm, Polyamide 66, red
1918570000	SF 00/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 3 mm, Polyamide 66, red
1918670000	SF 2/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 3.5 mm, Polyamide 66, red
1918900000	SF 3/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 4.5 mm, Polyamide 66, red
1919010000	SF 4,5/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 7.5 mm, Polyamide 66, red
1919070000	SF 4/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 5.7 mm, Polyamide 66, red
1919130000	SF 5/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 7.5 mm, Polyamide 66, red
1919180000	SF 6/21 NEUTRAL RT V2	Conductor markers, L x W: 21 x 8.5 mm, Polyamide 66, red